

HXHLQ-H2A43

Cavity Diplexer

Technical Data Sheet

S/N	Item	Parameters	
		RX	TX
1	Center Frequency(F0)	915MHz	965MHz
2	Pass Band Bandwidth	900 ~ 930MHz	950 ~ 980MHz
3	Pass Band Insertion Loss	≤1.0dB	≤1.0dB
4	Pass Band Ripple	≤0.5dB	≤0.5dB
5	Pass Band VSWR	≤1.3:1	≤1.3:1
6	Stop Band Attenuation	≥60dB @ 950 ~ 980MHz	≥60dB @ 900 ~ 930MHz
7	Impedance	50 Ohms	
8	Power	30W Max.	
9	Connectors	SMA-Female	
10	Surface Finish	Painted Black	
11	Port Sign	Port 1: ANT ; Port 2: RX ; Port 3: TX	
12	Temperature Range	-30℃ ~ +70℃	
13	Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
14	Dimensions	140*107*36mm	
15	Net weight	TBD	

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.7mm)

