


HXLBQ-DTA859

Cavity Band Pass Filter

Technical Data Sheet

S/N	Item	Parameters	
1	Center Frequency(F0)	2725MHz	
2	Pass Band Frequency	2600 ~ 2850MHz **	
3	Pass Band Insertion Loss	≤1.5dB	
4	Pass Band Ripple	≤0.7dB	
5	Pass Band Return Loss	≥23dB	
6	Stop Band Rejection	≥80dB @ DC ~ 2350MHz ≥70dB @ 2350 ~ 2400MHz	≥80dB @ 3050 ~ 8500MHz
7	Impedance	50 Ohms	
8	Power Handling	30W Max.	
9	Connectors	SMA-Female	
10	Surface Finish	Painted Black	
11	Temperature Range	-30°C ~ +70°C	
12	Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
13	Dimensions	110*22*19mm	
14	Net weight	TBD	

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)



**** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.**