


HXLBQ-DTA832

Cavity Band Pass Filter

Technical Data Sheet

S/N	Item	Parameters	
1	Center Frequency(F0)	2243.5MHz	
2	Pass Band Frequency	2233.5 ~ 2253.5MHz **	
3	Pass Band Insertion Loss	≤1.5dB	
4	Pass Band Ripple	≤0.5dB	
5	Pass Band Return Loss	≥20dB	
6	Stop Band Attenuation	≥60dB @ DC ~ 2189MHz	≥60dB @ 2298 ~ 5000MHz
7	Impedance	50 Ohms	
8	Power Handling	20W Max.	
9	Connectors	SMA-Female	
10	Surface Finish	Painted Black	
11	Temperature Range	-30°C ~ +70°C	
12	Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
13	Dimensions	100*68*26mm	
14	Net weight	0.25 KG	

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.4mm)



** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.