


# HXLBQ-DTA1071

## Comb Band Pass Filter

### Technical Data Sheet

S/N	Item	Parameters	
1	Center Frequency(F0)	8000MHz	
2	Pass Band Frequency	5000 ~ 11000MHz **	
3	Pass Band Insertion Loss	≤1.0dB	
4	Pass Band Ripple	≤0.7dB	
5	Pass Band Return Loss	≥15dB	
6	Stop Band Rejection	≥80dB @ DC ~ 3200MHz ≥40dB @ 3200 ~ 4300MHz	≥40dB @ 11250 ~ 13000MHz
7	Impedance	50 Ohms	
8	Power Handling	5.0W Max.	
9	Connectors	SMA-Female	
10	Surface Finish	Painted Black	
11	Temperature Range	-30°C ~ +70°C	
12	Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
13	Dimensions	120*29*12.5mm	
14	Net weight	TBD	

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)



\*\* The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.