

- **Product Name: LC Band Pass Filter**
- **Model: HXLBQ-DTA750LC**
- **Frequency: 566~678MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency	622MHz	
● Pass Band Frequency	566 ~ 678MHz **	
● Pass Band Insertion Loss	≤1.8dB	
● Pass Band Ripple	≤0.5dB	
● Pass Band Return Loss	≥14dB	
● Stop Band Rejection	≥50dB @ DC ~ 455MHz	≥50dB @ 840 ~ 1500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
● Dimensions	60*24*15mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

