

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA776LC
- **Frequency:** 170~230MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	200MHz	
● Pass Band Frequency	170 ~ 230MHz **	
● Pass Band Insertion Loss	≤1.4dB	
● Pass Band Ripple	≤0.6dB	
● Pass Band VSWR	≤1.4:1	
● Stop Band Rejection	≥40dB @ DC ~ 130MHz	≥40dB @ 270 ~ 800MHz
● Impedance	50 Ohms	
● Power Handling	1.0W Max.	
● Connectors	SMA-Male / SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
● Dimensions	40*18*13mm	
● Net weight	0.025 KG	

\*\* The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

