

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA535LC
- **Frequency:** 600~900MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	750MHz	
● Pass Band Frequency	600 ~ 900MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.6dB	
● Pass Band VSWR	≤1.5:1	
● Stop Band Rejection	≥40dB @ DC ~ 350MHz	≥70dB @ 1200 ~ 2700MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
● Dimensions	60*22*15mm	
● Net weight	TBD	
● <b>Outline Drawing:</b> (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

