

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA895LC
- **Frequency:** 250~350MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	300MHz
● Pass Band Frequency	250 ~ 350MHz **
● Pass Band Insertion Loss	≤1.8dB
● Pass Band Ripple	≤0.8dB
● Pass Band VSWR	≤1.4:1
● Stop Band Rejection	≥40dB @ DC ~ 200MHz ≥40dB @ 435 ~ 1500MHz
● Impedance	50 Ohms
● Power Handling	1.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Material	Housing: 6061 Aluminum alloy Connectors: Stainless Steel Cover: LY12 Aluminum alloy Other screw: Stainless Steel
● Dimensions	40*18*13mm
● Net weight	0.025 KG

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

