

- **Product Name:** LC Band Rejection Filter
- **Model:** HXLBQ-DZA191LC
- **Frequency:** 73~75MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

| Technical Data Sheet | |
|---|---|
| Item | Parameters |
| ● Stop Band Center Frequency | 74MHz |
| ● Stop Band Frequency | 73 ~ 75MHz |
| ● Stop Band Attenuation | ≥60dB |
| ● Pass Band Frequency | DC ~ 63MHz , 85 ~ 200MHz |
| ● Pass Band Insertion Loss | ≤2.0dB |
| ● Pass Band VSWR | ≤1.8:1 |
| ● Impedance | 50 Ohms |
| ● Power Handling | +15dBm Max. |
| ● Connectors | SMA-Female |
| ● Surface Finish | Painted Black |
| ● Temperature Range | -30°C ~ +70°C |
| ● Material | Housing: 6061 Aluminum alloy Connectors: Stainless Steel Cover: LY12 Aluminum alloy Other screw: Stainless Steel |
| ● Dimensions | 30*18*13mm |
| ● Net weight | 0.02KG |
| ● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm) | |

