

- **Product Name:** LC Band Rejection Filter
- **Model:** HXLBQ-DZA210LC
- **Frequency:** 300~450MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

| Technical Data Sheet | |
|----------------------------|---|
| Item | Parameters |
| ● Stop Band Frequency | 300 ~ 450MHz |
| ● Stop Band Attenuation | ≥40dB |
| ● Pass Band Frequency | DC ~ 240MHz , 550 ~ 1000MHz |
| ● Pass Band Insertion Loss | ≤2.0dB |
| ● Pass Band VSWR | ≤1.8:1 |
| ● Impedance | 50 Ohms |
| ● Power Handling | 1.0W Max. |
| ● Connectors | SMA-Female |
| ● Surface Finish | Painted Black |
| ● Temperature Range | -30°C ~ +70°C |
| ● Material | Housing: 6061 Aluminum alloy Connectors: Stainless Steel Cover: LY12 Aluminum alloy Other screw: Stainless Steel |
| ● Dimensions | 30*18*13mm |
| ● Net weight | 0.02KG |

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

