

- Model: HXLBQ-DZA208
- Product Name: Cavity Band Rejection Filter
- Frequency: 3300~4200MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Stop Band Frequency	3300 ~ 4200MHz	
● Stop Band Attenuation	≥50dB	
● Pass Band Frequency	DC ~ 3030MHz , 4470 ~ 8000MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band VSWR	≤1.7:1 (Typical: ≤1.5:1)	
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30℃ ~ +70℃	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	173*30*11mm	
● Net weight	0.141 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

