

- **Model:** HXLBQ-DTA737
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2061~2069MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2065MHz	
● Pass Band Frequency	2061 ~ 2069MHz	
● Pass Band Insertion Loss	≤1.3dB	
● Pass Band Ripple	≤0.2dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥40dB @ DC ~ 2046MHz	≥40dB @ 2084 ~ 6000MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	100*68*26mm	
● Net weight	0.252 KG	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.4mm)

