

- **Model: HXLBQ-DTA675**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 2700~3000MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	2850MHz	
● Pass Band Frequency	2700 ~ 3000MHz **	
● Pass Band Insertion Loss	≤1.2dB	
● Pass Band Ripple	≤0.5dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 2545MHz	≥40dB @ 3070 ~ 3140MHz
	≥40dB @ 2545 ~ 2630MHz	≥80dB @ 3140 ~ 9500MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	130*22*20mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

