

- **Model:** HXLBQ-DTA1090
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 7228.3 ~ 7248.3MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	7238.3MHz	
● Pass Band Frequency	7228.3 ~ 7248.3MHz **	
● Pass Band Insertion Loss	≤0.7dB	
● Pass Band Ripple	≤0.05dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 5378MHz	≥50dB @ 7998 ~ 9098MHz
	≥50dB @ 5378 ~ 6478MHz	≥80dB @ 9098 ~ 27000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Male / SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30℃ ~ +70℃	
● Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	40*16*8mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

●**Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: $\pm 0.3\text{mm}$)

