

- **Model:** HXLBQ-DTA147
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1805~1880MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1842.5MHz	
● Pass Band Frequency	1805 ~ 1880MHz	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Attenuation	≥50dB @ DC ~ 1795MHz	≥50dB @ 1890 ~ 3000MHz
● Impedance	50 Ohms	
● Power	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: 6061 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	150*63*31mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

