

●Model: HXHLQ-H5A12

●Product Name: Five Frequency Combiner

★High Isolation

★Low Pass Band Insertion Loss

★Customizable Design

★High Reliability

Technical Data Sheet

序号	指标项目(Parameters)	端口 1	端口 2	端口 3	端口 4	端口 5
1	工作频率(Frequency Range)	1128~1280MHz	1400~1460MHz	1520~1620MHz	2400~2500MHz	5700~5900MHz
2	插入损耗(Insertion Loss)	≤1.5dB	≤1.5dB	≤1.5dB	≤1.5dB	≤1.5dB
3	端口隔离(Ports Isolation)	≥40dB@1128~1280MHz, 1400~1460MHz, 1520~1620MHz			≥60dB@2400~2500MHz, 5700~5900MHz	
4	驻波比(VSWR)	≤1.7:1				
5	功率容量(Power Handling)	20W				
6	接头类型(Connectors)	SMA-Female				
7	端口阻抗(Ports Impedance)	50 OHM				
8	工作温度(Temperature)	-10℃~+60℃				
9	表面处理(Surface Finish)	本色导电氧化（Natural Conductive Oxidation）				

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±1.0mm)

