

- **Model:** HXLBQ-DTA163
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1345~1385MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	1365MHz	
● Pass Band Frequency	1345 ~ 1385MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Attenuation	≥50dB @ F0±120MHz (DC ~ 1245MHz , 1485 ~ 3000MHz)	
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	N-Male / N-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	98*35*20mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

