

- **Model:** HXLBQ-DTA252
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1280~1380MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	1330MHz	
● Pass Band Frequency	1280 ~ 1380MHz	
● Pass Band Insertion Loss	≤0.8dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Attenuation	≥60dB @ DC ~ 1130MHz	≥60dB @ 1470 ~ 3500MHz
● Impedance	50 Ohms	
● Power Handling	50W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	180*43*30mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

