

- **Model:** HXLBQ-DTA287X
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1260~1340MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	1300MHz	
● Pass Band Bandwidth	±40MHz (1260 ~ 1340MHz)	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band Ripple	≤1.0dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Rejection	≥30dB @ DC ~ 1240MHz	≥30dB @ 1360 ~ 3500MHz
● Impedance	50 Ohms	
● Power	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
● Dimensions	212*43*25mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.7mm)		

