

- **Model:** HXLBQ-DTA351
- **Product Name:** Comb Band Pass Filter
- **Frequency:** 9250~11250MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	10250MHz	
● Pass Band Frequency	9250 ~ 11250MHz	
● Pass Band Insertion Loss	≤0.8dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥80dB @ DC ~ 7700MHz	≥80dB @ 12600 ~ 26000MHz
● Impedance	50 Ohms	
● Power Handling	5W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
● Dimensions	70*16*9mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

