

- **Product Name:** LC Band Pass Filter
- **Model:** HXLBQ-DTA844LC
- **Frequency:** 1495~1505MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1500MHz	
● Pass Band Bandwidth	10MHz (1495 ~ 1505MHz) **	
● Pass Band Insertion Loss	≤3.5dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band VSWR	≤1.4:1	
● Stop Band Rejection	≥25dB @ DC ~ 1400MHz	≥25dB @ 1600 ~ 3000MHz
● Impedance	50 Ohms	
● Power Handling	1.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	40*18*13mm	
● Net weight	0.025 KG	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

