

- **Model:** HXLBQ-DTA395
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 3300~3800MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	3550MHz	
● Pass Band Frequency	3300 ~ 3800MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.5dB	
● Pass Band VSWR	≤1.22:1	
● Stop Band Rejection	≥50dB @ DC ~ 3100MHz	≥50dB @ 4000 ~ 8000MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	120*24*21mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

