

- **Model:** HXLBQ-DTA442
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1850~1910MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1880MHz	
● Pass Band Frequency	1850 ~ 1910MHz	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band Ripple	≤1.2dB	
● Pass Band VSWR	≤1.22:1	
● Stop Band Rejection	≥40dB @ DC ~ 1840MHz	≥40dB @ 1920 ~ 4000MHz
● Impedance	50 Ohms	
● Power	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30℃ ~ +70℃	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	92*92*26mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

