

- **Model:** HXLBQ-DTA513
- **Product Name:** Comb Band Pass Filter
- **Frequency:** 6.3~7.8GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	7.05GHz	
● Pass Band Frequency	6.3 ~ 7.8GHz	
● Pass Band Insertion Loss	≤1.2dB	
● Pass Band Ripple	≤0.6dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥80dB @ DC ~ 5.55GHz	≥50dB @ 8.2 ~ 8.4GHz
	≥50dB @ 5.55 ~ 5.9GHz	≥80dB @ 8.4 ~ 19GHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: H62 Copper alloy	Connectors: Stainless Steel
	Cover: H62 Copper alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	90*16*11mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

