

- **Model:** HXLBQ-DTA569
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2200~2210MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2205MHz	
● Pass Band Frequency	2200 ~ 2210MHz	
● Pass Band Insertion Loss	≤0.6dB	
● Pass Band Ripple	≤0.2dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥30dB @ DC ~ 2165MHz	≥30dB @ 2245 ~ 4500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	93*93*27mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

