

- **Model:** HXLBQ-DZA261
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 2300~2500MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Stop Band Frequency	2300 ~ 2500MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 2240MHz , 2530 ~ 6000MHz
● Pass Band Insertion Loss	≤1.5dB (at the corner: 2.0dB Max.)
● Pass Band VSWR	≤1.5:1 @ DC ~ 2240MHz , 2530 ~ 5400MHz ≤1.6:1 @ 5400 ~ 6000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Material	Housing: 6061 Aluminum alloy Connectors: Stainless Steel Cover: LY12 Aluminum alloy Other screw: Stainless Steel Tuning screw: H62 Copper alloy
● Dimensions	209*37*22mm
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

