

- **Product Name:** High Pass Filter
- **Model:** HXLBQ-GTA49
- **Frequency:** 1.75~10GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet		
Item	Parameters	
● Cut Off Frequency	1.75GHz	
● Pass Band Frequency	1.75 ~ 10GHz	
● Pass Band Insertion Loss	$\leq 2.0\text{dB @ } 1.75 \sim 1.9\text{GHz}$ $\leq 1.0\text{dB @ } 1.9 \sim 10\text{GHz}$	
● Pass Band VSWR	$\leq 1.5:1$	
● Stop Band Attenuation	$\geq 60\text{dB @ DC} \sim 1.47\text{GHz}$	
● Impedance	50 Ohms	
● Power Handling	15W Max.	
● Connectors	SMA-Female	
● Surface Finish	Guide Oxygen or Painted Black	
● Temperature Range	$-55^{\circ}\text{C} \sim +85^{\circ}\text{C}$	
● Material	Housing: 6061 Aluminum alloy screw: Stainless Steel Connectors: Stainless Steel	
● Dimensions	68*30*10mm	
● Net weight	0.04 KG	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: $\pm 0.3\text{mm}$)

