

- **Product Name:** High Pass Filter
- **Model:** HXLBQ-GTA71
- **Frequency:** 10~24GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet		
Item	Parameters	
● Cut Off Frequency	10GHz	
● Pass Band Frequency	10 ~ 24GHz	
● Pass Band Insertion Loss	$\leq 2.0\text{dB @ } 10 \sim 10.5\text{GHz}$ $\leq 1.0\text{dB @ } 10.5 \sim 24\text{GHz}$	
● Pass Band VSWR	$\leq 1.5:1$	
● Stop Band Attenuation	$\geq 60\text{dB @ DC} \sim 9.17\text{GHz}$	
● Impedance	50 Ohms	
● Power Handling	15W Max.	
● Connectors	SMA-Female	
● Surface Finish	Guide Oxygen or Painted Black	
● Temperature Range	$-55^{\circ}\text{C} \sim +85^{\circ}\text{C}$	
● Material	Housing: 6061 Aluminum alloy	screw: Stainless Steel
	Connectors: Stainless Steel	
● Dimensions	28*22*10mm	
● Net weight	0.02 KG	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: $\pm 0.3\text{mm}$)

