



- **Product Name:** High Pass Filter
- **Model:** HXLBQ-GTA97
- **Frequency:** 5.3~24GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet		
Item	Parameters	
● Pass Band Frequency	5.3 ~ 24GHz	
● Pass Band Insertion Loss	$\leq 1.8\text{dB @ } 5.3 \sim 5.7\text{GHz}$ $\leq 1.0\text{dB @ } 5.7 \sim 24\text{GHz}$	
● Pass Band VSWR	$\leq 1.6:1$	
● Stop Band Rejection	$\geq 40\text{dB @ } \text{DC} \sim 4.58\text{GHz}$	
● Impedance	50 Ohms	
● Power Handling	15W Max.	
● Connectors	SMA-Female	
● Surface Finish	Guide Oxygen or Painted Black	
● Temperature Range	$-30^{\circ}\text{C} \sim +70^{\circ}\text{C}$	
● Material	Housing: 6061 Aluminum alloy	screw: Stainless Steel
	Connectors: Stainless Steel	
● Dimensions	23*16*10mm	
● Net weight	0.015 KG	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: $\pm 0.3\text{mm}$)

