

- **Model: HXLBQ-DTA697**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 2300~2400MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	2350MHz	
● Pass Band Frequency	2300 ~ 2400MHz **	
● Pass Band Insertion Loss	≤1.3dB	
● Pass Band Ripple	≤0.6dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥90dB @ DC ~ 2200MHz	≥90dB @ 2500 ~ 4500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: Stainless Steel Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	188*28*25mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

