

- **Model: HXLBQ-DTA763**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 2846~2866MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	2856MHz	
● Pass Band Frequency	2846 ~ 2866MHz	
● Pass Band Insertion Loss	≤3.2dB	
● Pass Band Ripple	≤0.65dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 2796MHz	≥40dB @ 2886 ~ 2916MHz
	≥40dB @ 2796 ~ 2826MHz	≥80dB @ 2916 ~ 12000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	0°C ~ +50°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	120*20*17mm	
● Net weight	0.082 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

