

- **Model:** HXLBQ-DTA800
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 9.0~10.0GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	9.5GHz	
● Pass Band Frequency	9.0 ~ 10GHz	
● Pass Band Insertion Loss	≤0.6dB	
● Pass Band Ripple	≤0.25dB	
● Pass Band VSWR	≤1.15:1	
● Stop Band Rejection	≥45dB @ DC ~ 8.5GHz	≥45dB @ 10.5 ~ 23.5GHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	70*16*9mm	
● Net weight	0.065 KG	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

