

- **Model:** HXLBQ-DTA805
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 927.5 ~ 932.5MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	930MHz	
● Pass Band Frequency	927.5 ~ 932.5MHz **	
● Pass Band Insertion Loss	≤2.5dB	
● Pass Band Ripple	≤0.7dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥40dB @ DC ~ 920.5MHz	≥40dB @ 939.5 ~ 3000MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Male / SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	95*65*41mm	
● Net weight	0.378 KG	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

