

- **Model: HXLBQ-DTA863**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1700~2100MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1900MHz	
● Pass Band Frequency	1700 ~ 2100MHz **	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.5dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 1370MHz	≥75dB @ 2300 ~ 2320MHz
	≥50dB @ 1370 ~ 1500MHz	≥80dB @ 2320 ~ 6000MHz
● Impedance	50 Ohms	
● Power	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Resonant column: H59 Copper alloy
	Cover: LY12 Aluminum alloy	Connectors: Stainless Steel
	Tuning screw: H62 Copper alloy	Other screw: Stainless Steel
● Dimensions	120*25*23mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

