

- **Model: HXLBQ-DTA875**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 3700~4200MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	3950MHz	
● Pass Band Frequency	3700 ~ 4200MHz	
● Pass Band Insertion Loss	≤1.4dB	
● Pass Band Ripple	≤0.8dB	
● Pass Band VSWR	≤1.15:1	
● Stop Band Rejection	≥80dB @ DC ~ 3550MHz	≥80dB @ 4350 ~ 13000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	160*21*15mm	
● Net weight	0.14 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

