

- **Model: HXLBQ-DTA904**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 9200~9500MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	9350MHz	
● Pass Band Frequency	9200 ~ 9500MHz **	
● Pass Band Insertion Loss	≤1.2dB	
● Pass Band Ripple	≤0.6dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥50dB @ DC ~ 8990MHz	≥50dB @ 9710 ~ 19000MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	65*36*10mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

