

- **Model:** HXLBQ-DTA927
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 14700~14800MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	14750MHz	
● Pass Band Frequency	14700 ~ 14800MHz **	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 14320MHz	≥60dB @ 15100 ~ 15180MHz
	≥60dB @ 14320 ~ 14400MHz	≥80dB @ 15180 ~ 30000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: H62 Copper alloy	Connectors: Stainless Steel
	Cover: H62 Copper alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	80*16*9mm	
● Net weight	0.081 KG	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

