

- **Model:** HXLBQ-DTA988
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 4200~4300MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	4250MHz	
● Pass Band Frequency	4200 ~ 4300MHz **	
● Pass Band Insertion Loss	≤1.1dB	
● Pass Band Ripple	≤0.18dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 3990MHz	≥50dB @ 4450 ~ 4510MHz
	≥50dB @ 3990 ~ 4050MHz	≥80dB @ 4510 ~ 13000MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: H62 Copper alloy	Connectors: Stainless Steel
	Cover: H62 Copper alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	90*17*14mm	
● Net weight	0.13 KG	

**The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

