

- **Model:** HXLBQ-DTA833X
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 3170~3330MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	3250MHz	
● 3.0dB Bandwidth	160MHz (3170 ~ 3330MHz) [Deviation: ±20MHz @ Temperature Range: +20°C ~ +30°C]	
● Insertion Loss @ F0	≤1.2dB @ 3250MHz	
● Return Loss	≥23dB @ 3200 ~ 3300MHz	
● Stop Band Rejection	≥80dB @ DC ~ 3000MHz	≥45dB @ 3400 ~ 3500MHz
	≥45dB @ 3000 ~ 3100MHz	≥80dB @ 3500 ~ 7000MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	120*21*19mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

