

- **Model:** HXLBQ-DTA1180
- **Product Name:** Comb Band Pass Filter
- **Frequency:** 2500 ~ 4500MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters	
● Center Frequency(F0)	3500MHz	
● Pass Band Bandwidth	2000MHz (2500 ~ 4500MHz)	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.6dB	
● Pass Band Return Loss	≥18dB	
● Stop Band Rejection	≥80dB @ DC ~ 1920MHz ≥50dB @ 1920 ~ 2180MHz	≥50dB @ 4700 ~ 4770MHz ≥80dB @ 4770 ~ 10000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Dimensions	150*27*18mm	
● Net weight	TBD	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- **Material**
  - Housing: 6061 Aluminum alloy
  - Cover: LY12 Aluminum alloy
  - Tuning screw: H62 Copper alloy
  - Connectors: Stainless Steel
  - Other screw: Stainless Steel

