

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA78**
- **Frequency: 13.5~24.5GHz**

- ★ **High Stop Band Rejection**
- ★ **Low Pass Band Insertion Loss**
- ★ **Customizable Design**
- ★ **Small Size**

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	13.5GHz
● Pass Band Frequency	13.5 ~ 24.5GHz
● Pass Band Insertion Loss	≤2.0dB @ 13.5 ~ 14.2GHz ≤1.0dB @ 14.2 ~ 24.5GHz
● Pass Band VSWR	≤1.6:1
● Stop Band Attenuation	≥60dB @ DC ~ 12.4GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.02 KG
● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ Material <ul style="list-style-type: none"> ● Housing: Aluminum alloy ● Screw: Stainless Steel 	<ul style="list-style-type: none"> ● Connectors: Stainless Steel ● Dimensions: 26*20*10mm

