

- **Model:** HXLBQ-DTA1051
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 617~652MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	634.5MHz
● Pass Band Frequency	617 ~ 652MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band Ripple	≤1.0dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥80dB @ DC ~ 587MHz ≥80dB @ 682 ~ 1500MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	0.555 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

◆ **Material**

- Housing: 6061 Aluminum alloy
- Cover: LY12 Aluminum alloy
- Tuning screw: H62 Copper alloy
- Connectors: Stainless Steel
- Working Environment: Indoor
- Dimensions: 148*76*49mm

