

- **Model:** HXLBQ-DTA835
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2454~2474MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	2464MHz
● Pass Band Frequency	2454 ~ 2474MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.5dB
● Pass Band Return Loss	≥20dB
● Stop Band Attenuation	≥60dB @ DC ~ 2409.5MHz ≥60dB @ 2518.5 ~ 5000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.25 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

◆ **Material**

- Housing: 6061 Aluminum alloy
- Connectors: Stainless Steel
- Cover: LY12 Aluminum alloy
- Working Environment: Indoor
- Tuning screw: H62 Copper alloy
- Dimensions: 100*68*33mm

