- **Model：HXLBQ-DZA285X**
- **Product Name：Cavity Band Rejection Filter**
- **Frequency：859~930MHz**

★High Stop Band Rejection
★Low Pass Band Insertion Loss
★Customizable Design
★High Reliability

Technical Data Sheet	
Item	**Parameters**
● Stop Band Frequency	859 ~ 930MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 824MHz , 965 ~ 2700MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.7:1
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	0℃ ~ +40℃
● Net weight	TBD

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

◆Material

- ●Housing: 6061 Aluminum alloy
- ●Cover: LY12 Aluminum alloy
- ●Tuning screw: H62 Copper alloy
- ●Connectors: Stainless Steel
- ●Working Environment: Indoor
- ●Dimensions: 265*80*28mm



Tel:+86-029-85450833 FAX:+86-029-85450833 E-mail:sales_hxwb@163.com E-mail: sales@xahxmicrowave.com
http://www.xahxmicrowave.com http://www.hx-microwave.com Add:Yanta District, Xi'an, China