

- **Model:** HXLBQ-DZA284
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 777~798MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	777 ~ 798MHz
● Stop Band Attenuation	≥40dB
● Pass Band Frequency	DC ~ 750MHz , 825 ~ 2300MHz
● Pass Band Insertion Loss	≤1.5dB (at the corner: 2.0dB Max.)
● Pass Band VSWR	≤1.6:1
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-10°C ~ +50°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- ◆ **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: Stainless Steel
 - Working Environment: Indoor
 - Dimensions: 248*95*28mm

