

- **Model:** HXLBQ-DZA263
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 4000~5000MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Stop Band Frequency	4000 ~ 5000MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 3700MHz , 5300 ~ 10300MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.7:1
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	+15°C ~ +30°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                               |
|-------------------|----------------------------------|-------------------------------|
| ◆ <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: Stainless Steel |
|                   | ● Cover: LY12 Aluminum alloy     | ● Working Environment: Indoor |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 141*32*16mm     |

