

- **Model:** HXLBQ-DTA192
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2085~2115MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

### Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	2100MHz
● Pass Band Frequency	2085 ~ 2115MHz
● Pass Band Insertion Loss	≤3.0dB
● Pass Band Ripple	≤0.7dB
● Pass Band VSWR	≤1.3:1
● Stop Band Attenuation	≥60dB @ DC ~ 2040MHz      ≥60dB @ 2160 ~ 6000MHz
● Impedance	50 Ohms
● Power Handling	5W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

#### ● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |  |
|-------------------|----------------------------------|--|
| ● <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: H59 Copper, Plated ternary alloy |
|                   | ● Cover: LY12 Aluminum alloy     | ● Other screw: Stainless Steel                 |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 113*28*20mm                      |

