

- **Model:** HXLBQ-DZA63
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 1920~1980MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	1920-1980MHz
● Stop Band Attenuation	≥35dB
● Pass Band Frequency	DC ~ 1900MHz , 2000 ~ 4500MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band VSWR	≤1.5:1
● Impedance	50 Ohms
● Power	50W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	0.5KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|------------------------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 225*55*22mm |

