

- **Model:** HXLBQ-DZA241
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 758~803MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	758 ~ 803MHz
● Stop Band Attenuation	≥60dB
● Pass Band Frequency	DC ~ 735MHz , 849 ~ 2300MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.5:1 @ DC ~ 735MHz , 849 ~ 2000MHz ≤1.7:1 @ 2000 ~ 2300MHz
● Impedance	50 Ohms
● Power	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	1.0 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 265*90*28mm |

