

- **Model:** HXLBQ-DTA159
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 870~880MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	875MHz
● Pass Band Frequency	870 ~ 880MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥45dB @ DC ~ 855MHz ≥45dB @ 895 ~ 2700MHz
● Impedance	50 Ohms
● Power	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|------------------------------|--|
| ● Material | ● Housing: Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: Copper alloy | ● Dimensions: 164*50*30mm |

